



ZELA Fire Rated Deep Fixed Downlight



- IP65 (front face)
- Size 86x64mm
- Min cavity depth 190mm*
- Cut-out 73mm

*Fire Rated downlights must not be installed into a cavity of less than 190mm as tested to AS 1530.4:2014




Diffuser options:



Lens diffuser
Beam 9° 15° 20°
Spot lighting

Prismatic diffuser
Beam 40° 55°
General lighting

Trim options:



15° only available in CCT 2700K, 3000K or 4000K

FITTING TYPE	CODE	W	BEAM ANGLE/LUMENS					IC	CCT	CUT-OUT	CRI	DIMMABLE	DIMENSIONS DIA x Height
			9°	15°	20°	40°	55°						
DEEP FIXED	DLZFRDF11W	11W	n/a	640-700	770-900	830-970	830-970	CA135	2400K 2700K 3000K 4000K	Ø73mm	>90	TRIAC DALI	Ø86 x 64mm
DEEP FIXED S-DIM	DLZFRDF11WSD		40°	55°					3000-1850K				
			740	710									



Get in touch

U4 / 61-71 Beauchamp Rd,
Matraville NSW 2036

02 9317 4177
0425 350 698

sales@tecled.com.au
Victoria@tecled.com.au

Follow us

