


ZELA Fixed Downlight



- IP65 (front face)
- Size 65x43mm
- Cut-out 52-57mm
- Min hole depth 100mm*

*Specification is for ceiling material ≤ 13mm.



Lens diffuser
Beam 9° 15° 20°
Spot lighting



Prismatic diffuser
Beam 40° 55°
General lighting

Trim options:



Textured white



Textured black

*9° only available in CRI 97

*9° & 15° only available in CCT 2700K, 3000K or 4000K

FITTING TYPE	CODE	W	BEAM ANGLE/LUMENS					IC	CCT	CUT-OUT	CRI	DIMMABLE	DIMENSIONS DIA x Height
			9°	15°	20°	40°	55°						
FIXED	DLZELAF4.3W	4.3W	260 - 280	280 - 310	350 - 400	360 - 420	350 - 410	4	2400K 2700K 3000K 4000K	Ø52-57mm	>90	TRIAC DALI	65 x 43mm
	DLZELAF6.4W	6.4W	370 - 400	400 - 440	490 - 570	520 - 600	500 - 580	n/a					
	DLZELAF9.4W	9.4W	n/a	550 - 600	670 - 780	710 - 820	680 - 790						
FIXED S-DIM	DLZELAF6.4WSD	6.4W	40° 450		55° 450			4	3000-1850K				
	DLZELAF9.4WSD	9.4W	620		620			n/a					



Get in touch

U4 / 61-71 Beauchamp Rd,
Matraville NSW 2036

02 9317 4177
0425 350 698

sales@tecled.com.au
Victoria@tecled.com.au

Follow us

